

NEW IN OUR PRODUCT RANGE

until revocation

MMA Inverter ATM 1600 PFC and ATM 2000 PFC

The inverters ATM 1600 PFC and ATM 2000 PFC are back in our product range. With PFC technology and new design. The functions such as Arc-Force, Hot-Start and Anti-Stick are controlled manually. The welding of TIG with Lift-Arc ignition is also possible.



JAVAC Deutschland GmbH
www.javac-deutschland.de
info@javac-deutschland.de

SPECIALIST SHOP

Features

- PFC technology
- With Lift TIG mode
- Anti-Stick, Arc-Force, Hot-Start, VRD
- Overheating, overcurrent, undervoltage protection
- Generator-compatible
- MMA /Lift TIG mode
- Light and handy



Scope of delivery:
1 Earth cable
1 Electrode cable
1 Case

Model	ATM 1600 PFC	ATM 2000 PFC
Supply voltage	1 - 230V ± 10%, 50/60 Hz	1 - 230V ± 10%, 50/60 Hz
Power	5,1 kW	6,8 kW
Effective current	14,5 A	20A
Nominal input current	23 A	31A
Duty cycle	MMA 40% 160 A 60% 135 A 100% 105 A	MMA 30% 200A 60% 165A 100% 135A
No-load voltage	14,5 V	14,5 V
Welding current range	10 - 160 A	10 - 200A
Insulation class	H	H
Protection class	IP 23	IP 23
Measurements (LxWxH)	380x136x250 mm	380x136x250 mm
Weight	6,1 kg	6,1 kg
Cooling	AF	AF
Item no.	02.01.02.00160	02.01.02.00210

Subject to misprints, errors and technical changes! 08.05.2020

For more info click on us:

<http://www.javac.org> → Current Offers

Industriestraße 29/2
D-73340 Amstetten

Tel. +49 (0)73 31 - 30 58 0
Fax +49 (0)73 31 - 30 58 58

Order Processing
+49(0)73 31 - 30 58 20

Technical information
+49(0)73 31 - 30 58 24

